Correspondence Address: Standard House, 2nd Floor, Indira Gandhi Marg, Jamnagar 361001 Tel.: (0288) 2553648, 2770060, 098248 50777 Fax: (0288) 2553873 Email: kmkotak@kotakgroups.com

TEST CERTIFICATE

IS:8887:2004

Sample Batch No 22/17

Product – Emulsion MS Dt. 13-12-2017

	Dit 10 12 -01.	
Properties	Requirement	Result
Residue on 600 micron sieve	0.05 Max	0.03
Viscosity by Saybolt Furol viscometer at 25 deg. C	50-300	64
Coagulation at low temperature	Nil	Nil
Storage Stability after 24 hrs	4 1 % max	< 1
Particle Charge	+ ve	+ ve
Coating ability and water resistance		
Coating Dry aggregate Coating After spraying	Good Fair	Good Fair
Coating Wet aggregate	Fair	Fair
Coating After spraying	Fair	Fair
Miscibility with water	No Coagulation	No Coagulation
Test on Residue		
Residue by evaporation min Penetration at 25 Deg. C Ductility at 27 Deg. C	65 60-150 50	66 101 55
Solubility in trichloroethylene (Min)	98	99.1

FOR, KOTAK ASPHALT LLP

THORISED SIGNATORY